

# ACRYLIC COLOR PACK

Solvent Based Tint Pack for Acrylic Sealers

## Product Description

Acrylic Color Pack is a high solids, concentrated, solvent based acrylic tint system specially formulated for solvent based acrylic sealers. Acrylic Color Pack is formulated with high quality, ultra fine particle pigments that easily disperses in solvent based acrylic sealers. Acrylic Color Pack is a superior choice to obtain a semi transparent stain or a solid opaque colored finish in most solvent based acrylic sealer systems.

## Benefits & Features

- An excellent choice of 14 colors (including black and white)
- Very economical and decorative way to seal a variety of concrete substrates.
- Reduces the cost of inventory stocking needs
- Very easy way to stain, as opposed to multiple steps of other stain systems

## Recommended Applications

Acrylic Color Pack is recommended for use on unsealed or untreated warehouse floors, garages, basements, docks, driveways, sidewalks, and any other concrete surface where a solid color sealing and dust proofing method is desired.

## Technical Information

Solids	Depends on Acrylic Sealer	Wet Appearance	Varies Depending on Color
Drying Time	1-2 Hours	Dry Appearance	Varies, High Gloss
Re-Coat Time	4-24 Hours	VOC Content	N/A
Foot Traffic	4-6 Hours	Blush Resistance	Good
Wheel Traffic	24-48 Hours	Solvent Resistance	Minimal
Application Temp	40°F - 85°F	Concrete Adhesion	Excellent

\*\*\*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

## Approximate Usage Rates

<u>Desired Finish</u>	<u>Approx. Amount Added to 1 Gallon</u>	<u>Approx. Amount Added to 5 Gallon</u>
Semi Transparent Stain	2 - 8 ounces	8 - 16 ounces
Solid Opaque Finish	8 ounces	32 ounces (1 quart)

\*Usage rates are suggested amounts only! Due to varying sealer compositions, substrates, surface texture, porosity and desired look a test area is recommended to achieve desired results.

## Shelf Life

Acrylic Color Pack has a shelf life of a minimum of one year in it's original, sealed, unopened container.

## Packaging

Acrylic Color Pack is packaged in quart cans only

**ORRVILLE**  
133 North Kohler Road  
Orrville, Ohio 44667  
(330) 682-5678

**CLEVELAND**  
7941 Granger Road  
Cleveland, Ohio 44125  
(216) 573-0770

**COLUMBUS**  
690 Harrison Drive  
Columbus, Ohio 43204  
(614) 253-3326



www.eco-cretesupply.com

## **Instructions for Use**

**Mixing:** Mix desired amount in a solvent based acrylic sealer for 1-2 minutes using a squirrel mixer prior to application. Allow any foam to settle prior to use. Material may separate during long term storage. Re-mix as needed.

**Please Note:** It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Usage and coverage rates may vary for all coatings and substrate depending on porosity, density, texture, etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and the transparency of the color may vary.

**Caution:** Do not add too much color! Apply a test area prior to job application for desired appearance. Over pig-menting may cause color float or streaking. Especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application as well as the composition of the solvent based acrylic sealer.

Check Acrylic Color Pack for compatibility with the solvent based acrylic sealer to be used prior to use!

## **Clean-Up**

Use Xylene. Dispose of containers in accordance with local and federal regulations.

## **Product Removal**

Dried, cured sealer may be removed with a commercial paint stripper, such as Nock Off or by using a diamond grinding method, sandblasting method or similar mechanical action.

## **Precautions & Limitations**

- Acrylic Color Pack will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- Keep away from open flames. Acrylic Color Pack is flammable and is very susceptible to ignition.
- Follow the instructions for the solvent based acrylic sealer that is to be used for application guidelines.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- Acrylic Color Pack was designed for new or old concrete and to be applied in thin coats, not one thick coat.
- Please be aware that this product when cured may be slippery when wet. Use anti-skid additive as needed.
- Acrylic Color Pack is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin Acrylic Color Pack. Improper thinning may cause sealer to delaminate in a short time frame.

## **Special Notes**

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

### **ORRVILLE**

133 North Kohler Road  
Orrville, Ohio 44667  
(330) 682-5678

### **CLEVELAND**

7941 Granger Road  
Cleveland, Ohio 44125  
(216) 573-0770

### **COLUMBUS**

690 Harrison Drive  
Columbus, Ohio 43204  
(614) 253-3326

