

UNIVERSAL PIGMENT PACKS

Iron Oxide Pigment

Product Description

Universal Pigment Pack is an economical system that allows you to stock 5 base colors to create 20 custom colors using our simple formula. Each color is packaged in 2.5 lb containers with individual measuring scoops, making the system easy to use. Universal Pigment Packs can be used to color most cementitious pre-packaged products including: overlay mix, countertop mix, concrete mix, mortar, grout, plaster, and many other products. By using the included measuring scoop you are able to create 4 different shades of color out of each container.

Benefits & Features

- Reclosable 2.5 lb container
- Stock only 5 colors to make 20 colors
- Most popular shades from all manufacturers
- Easily keep consistent colors from batch to batch
- UV-resistant color

Technical Information

VOC (Volatile Organic Compound) Content	0 grams/liter
Appearance	Dry Powder
Composition and Materials	Pigments are Red, Yellow, & Black Iron Oxides

Applications

- Mortar
- Overlays
- Countertops
- Bagged Concrete
- Plaster

Packaging

- 2.5 lb container
- Measuring scoop (designed to be used with 10-12 lb of Portland or masonry cement)

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

723 Taylor Avenue
Columbus, Ohio 43219
(614) 253-3326



Instructions for Use

1. Remove measuring scoop from container. (See Photo 1)
2. (Optional) Pour contents into larger bucket or container.
3. Overfill measuring scoop with pigment. (See Photo 2)
4. Using the palm of your hand, compact the dry pigment as much as possible. (See Photo 3)
5. Add additional pigment to overfill the scoop and compact again.
6. Compacted scoop of pigment is now ready for 1 batch or bag of cementitious material.
7. Additional scoops (up to 4 total) may be added to achieve additional colors. When using more than one scoop per bag, it is recommended that you measure out pigment for each bag or batch before you begin mixing. (See Photo 4)
8. A jobsite sample is always recommended.



Additives: DO NOT USE CALCIUM CHLORIDE! Plasticizers, water reducers, non-chloride accelerators, and air entraining products that are designed for colored concrete may be used.

Curing: DO NOT COVER, FOG OR WET CURE COLORED SURFACES.

Warranty: PROFESSIONAL USE ONLY. Product is intended for licensed concrete contractors, that have the experience and training to use this product. End user is responsible for product aptness and assumes all risks and liability. Obligations of the manufacturer will be limited to refunding the purchase price of replacing the product if deemed defective.

Clean-up

Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

Shelf Life

Indefinite when in its original, unopened container, stored at room temperature.

Special Notes

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

723 Taylor Avenue
Columbus, Ohio 43219
(614) 253-3326



www.eco-cretesupply.com